



RECEIVED  
JAN 07 2004  
TC 1700

AMENDMENTS TO THE CLAIMS

1. (Original) A method of making shingles comprising:  
providing a moving asphalt coated sheet having at least an overlay lane and an underlay lane;  
discharging blend drops of at least two color blends onto each lane, wherein at least one of the blend drops discharged onto the overlay lane has a different color blend from the color blends of all the blend drops discharged onto the underlay lane;  
discharging background granules onto the asphalt coated sheet to form a granule coated sheet; and  
removing excess granules from the granule coated sheet.
  
2. (Original) The method of claim 1 including:  
discharging blend drops of three color blends onto the overlay lane and discharging blend drops of three color blends onto the underlay lane;  
wherein at least one of the blend drops discharged onto the overlay lane has a different color blend from the color blends of all the blend drops discharged onto the underlay lane.
  
3. (Original) The method of claim 1 including:  
dividing the granule coated sheet into overlay and underlay strips; and  
laminating the overlay and underlay strips together to form shingles.
  
4. (Original) The method of claim 3, wherein one of the blend drops forms a shadow line on a tab or cutout of the shingle.

5. (Original) A method of making shingles comprising:
  - providing a moving asphalt coated sheet having an overlay lane, a middle lane and an underlay lane;
  - discharging blend drops of at least two color blends onto each lane, wherein each lane has a combination of color blends for the blend drops different from the combination of color blends for the blend drops of the other two lanes;
  - discharging background granules onto the asphalt coated sheet to form a granule coated sheet;
  - removing excess granules from the granule coated sheet;
  - dividing the granule coated sheet into continuous overlay, middle and underlay strips; and
  - laminating the continuous overlay, middle and underlay strips together to form trilaminate shingles.

6. (Original) The method of claim 5 in which:
  - the step of removing excess granules includes collecting excess granules in a backfall hopper that segregates excess granules from lane to lane; and
  - the step of applying background granules includes applying to each lane excess granules removed from that lane.

7 through 9. Cancelled